


MONUMENT RECORD
Corner ID: Rich_K13
Section Corner
Sections 16 & 21- T09N-R02W, 2nd P.M.
Richland Township, Monroe County, Indiana



EXISTING SURVEY HISTORY

Include as much detail and history of the corner as known at the time of perpetuation.

ORIGINAL GOVERNMENT SURVEY:

Year Surveyed: 1816 By: William Harris
Where filed or recorded: Original Notes Page 337
Original monument: Post
Bearing Trees or Reference Monuments:

Species	Dia.	Bearing	Distance
Beech	10"	N 61° E	5 Links
Sugar	9"	N 66° W	28 Links

Notes:

SUBSEQUENT CORNER RESTORATION:

Date Surveyed: 9/7/1983 By: Edmund O. Farkas
Where filed or recorded: M.C.S.O. Files
Original monument: Brass Cap and Rod
Bearing Trees or Reference Monuments:

I.D.	Dia.	Bearing	Distance
PK in Cherry	10"	S 48° E	19.86'
PK in Beech	15"	S 22° E	47.87'
Corner Post		West	16.50'

Notes:

SUBSEQUENT CORNER RESTORATION:

Date Surveyed: 1/25/2006 By: Kevin P. Enright
Where filed or recorded: M.C.S.O. Files
Original monument: Brass Spike
Bearing Trees or Reference Monuments:

I.D.	Dia.	Bearing	Distance
Fence Post		S 88° W	29.75'
Metal Post		N 32° E	38.75'
Mag in Beech	24"	S 18° E	47.75'

Notes:

SURVEY EVIDENCE FOUND: Include evidence found and weighed, search area or areas, search procedure, etc.
Date of Search: 11/9/21 By: J.R. & K.H. Monument Found: Brass Spike BTs or Reference Objects Found: Fence post to the West, T-Post to the Northeast, Beech to the Southeast Notes:

OTHER SURVEY HISTORY: Include details such as surveyor name, date, recording info, monument description, etc.

PERPETUATION RECORD

MONUMENT: Describe monument set or found (Include material type, scribing, distance above/below grade, dimensions.)
Brass Spike found 1 inch below grade


OTHER EVIDENCE: Describe corner location relative to nearby features and how to reach the corner location – note fences, roads, timber cutting lines, mow lines, clearings, plantings, streams, topo changes, etc.
Brass spike found near the North-South running centerline of Louden Road

THEORY OF LOCATION: Describe the theory of location for acceptance of this monument with reference to the recording information for the survey upon which this record is derived. Said recorded survey shall be certified by the same professional surveyor who certifies this document, shall identify and accept this monument, and shall have been recorded within (3) years of Form submittal.
Ties prepared by Monroe County Surveyor Edmund O. Farkas dated September 7th, 1983 show a brass cap and rod was set. Ties prepared by Monroe County Surveyor Kevin P. Enright dated January 25th, 2006 show a brass rod found. It is believed that these ties are referencing the same brass monument and this brass spike was found to be commonly accepted by surveys in the area and was accepted and held as said corner.


MONUMENT PRESERVATION: Describe work done to preserve existing monument. Stone mounds should be placed around monuments when stones are readily available. Paint corner stones but not the scribing. A Monroe County “PROTECT NEARBY SURVEY MARKER” sign shall be attached to a steel post when practicable. Note location and relation of corner to sign.
A Monroe County “PROTECT NEARBY SURVEY MARKER” sign was found on a wood fence post to the West of the brass spike

GEODETIC COORDINATES: Northing: 1442985.6, Easting: 3078426.9

BASIS OF GEODETIC COORDINATES: Describe equipment, date, and personnel used to collect coordinates, datum, epoch, geoid and zone.
Coordinates shown hereon were obtained from GPS observations utilizing the Indiana Real-Time Network (INCORS). Indiana West Zone, NAD83(2011) Epoch 2010.0000, State Plane Grid Coordinates, US Survey Feet. Geoid model G2012BU7. Datum NAD83_NO_TRANS and the use of a Topcon 302 Total Station by Jackson Rogers and Kyle Hazelman on November 9th, 2021.



MONUMENT RECORD
Corner ID: Rich_K13
Section Corner
Sections 16 & 21- T09N-R02W, 2nd P.M.
Richland Township, Monroe County, Indiana



WITNESS MONUMENT TIES: Describe at least three new BT's and/or witness objects established or work done to preserve existing evidence. The following procedures are provided for guidance. Please utilize professional judgment when choosing witness ties. All ties to BT's should be a magnetic nail and washer (state what kind) set in a hack mark at root crown (less than 12” above ground) perpendicular to center of tree unless otherwise noted. All monuments should be tied to at least three accessories with a minimum of 60° of separation. BTs should be healthy with a minimum DBH of 4”. BT description should include tree species, diameter at 4.5’ above ground, distance of nail above ground, and description of nail location (e.g.. SE side of root). Note bearing from monument to the center of the BT, distance to the nail. Other survey monuments that were located in the vicinity and their relation to the monument may also be included.

ID	Bearing	Distance	Description
<i>B</i>	<i>S 82° W</i>	<i>30.1’</i>	<i>Mag w/ Washer set 10” A.G. South side of 10” Dia. Wood Post</i>
<i>C</i>	<i>N 34° E</i>	<i>38.7’</i>	<i>T-Post</i>
<i>D</i>	<i>S 17° E</i>	<i>47.7’</i>	<i>Mag w/ Washer set 10” A.G. West side of 28” Dia. Beech</i>

Notes:

MONUMENT LOCATION SKETCH: Optional: Attach a sketch or aerial image. Monument sketch is not required for reimbursement.

PHOTO IDENTIFIED: Photograph close up photo of monument and a vicinity photo of the monument that includes the Monroe County “PROTECT NEARBY SURVEY MARKER” sign. Provide photo orientation and date. Additional photos may be included by clicking the “+” button at the end of the horizontal line.

Photo Date: *November 2021*



Photo Orientation & Description: *Looking North at K-13*



Photo Orientation & Description: *Looking West at K-13*

FIELD PERSONNEL:

Field Date: *11/9/21* By: *J.R. & K.H.* Project #: *21-157* Field Book: , page: Notes:

CERTIFICATION:


Professional Surveyor Name: *Eric L. Deckard*
Indiana Professional Surveyor No.: *29900012*
Firm Name: *Deckard Land Surveying*
Date: *12/03/21*

Signature:


[Signature]



Seal:







MONUMENT RECORD
Corner ID: **Rich_K13**
Section Corner
Sections 16 & 21- T09N-R02W, 2nd P.M.
Richland Township, Monroe County, Indiana



OFFICE USE ONLY

NOTICE TO PROCEED AND MONUMENT RECORD FORM ISSUED TO:			
Offeror Name: Eric L. Deckard		Firm Name: Deckard Land Surveying, LLC	
Phone: (812)961-0235		Email: Ericdeckard1@msn.com	
Corner Classification: Section Corner		Corner Coordinate Status: Perpetuated	
Issue Date: 7/12/22	Form Due Date: 7/21/22		Form Receipt Date: 7/21/2022

COUNTY SURVEYOR APPROVAL: <input checked="" type="checkbox"/> Yes, Signature:  <input type="checkbox"/> No, reasons for denial	Date: 7/19/22	Seal: 
--	----------------------	---

SURVEYOR REVIEW BOARD APPROVAL: <input checked="" type="checkbox"/> Yes, Signature:  <input type="checkbox"/> No, reasons for denial	Date: 7/19/22	Seal: 
---	----------------------	--